

## **Disclaimer**

This Report, including the data and information contained in this Report, is provided to you on an “as is” and “as available” basis at the sole discretion of the Government of Alberta and subject to the terms and conditions of use below (the “Terms and Conditions”). The Government of Alberta has not verified this Report for accuracy and does not warrant the accuracy of, or make any other warranties or representations regarding, this Report. Furthermore, updates to this Report may not be made available. Your use of any of this Report is at your sole and absolute risk.

This Report is provided to the Government of Alberta, and the Government of Alberta has obtained a license or other authorization for use of the Reports, from:

Shell Canada Energy, Chevron Canada Limited. and Marathon Oil Canada Corporation, for the Quest Project

(collectively the “Project”)

Each member of the Project expressly disclaims any representation or warranty, express or implied, as to the accuracy or completeness of the material and information contained herein, and none of them shall have any liability, regardless of any negligence or fault, for any statements contained in, or for any omissions from, this Report. Under no circumstances shall the Government of Alberta or the Project be liable for any damages, claims, causes of action, losses, legal fees or expenses, or any other cost whatsoever arising out of the use of this Report or any part thereof or the use of any other data or information on this website.

## **Terms and Conditions of Use**

Except as indicated in these Terms and Conditions, this Report and any part thereof shall not be copied, reproduced, distributed, republished, downloaded, displayed, posted or transmitted in any form or by any means, without the prior written consent of the Government of Alberta and the Project.

The Government of Alberta’s intent in posting this Report is to make them available to the public for personal and non-commercial (educational) use. You may not use this Report for any other purpose. You may reproduce data and information in this Report subject to the following conditions:

- any disclaimers that appear in this Report shall be retained in their original form and applied to the data and information reproduced from this Report
- the data and information shall not be modified from its original form
- the Project shall be identified as the original source of the data and information, while this website shall be identified as the reference source, and
- the reproduction shall not be represented as an official version of the materials reproduced, nor as having been made in affiliation with or with the endorsement of the Government of Alberta or the Project

By accessing and using this Report, you agree to indemnify and hold the Government of Alberta and the Project, and their respective employees and agents, harmless from and against any and all claims, demands, actions and costs (including legal costs on a solicitor-client basis) arising out of any breach by you of these Terms and Conditions or otherwise arising out of your use or reproduction of the data and information in this Report.

Your access to and use of this Report is subject exclusively to these Terms and Conditions and any terms and conditions contained within the Report itself, all of which you shall comply with. You will not use this Report for any purpose that is unlawful or prohibited by these Terms and Conditions. You agree that any other use of this Report means you agree to be bound by these Terms and Conditions. These Terms and Conditions are subject to modification, and you agree to review them periodically for changes. If you do not accept these Terms and Conditions you agree to immediately stop accessing this Report and destroy all copies in your possession or control.

These Terms and Conditions may change at any time, and your continued use and reproduction of this Report following any changes shall be deemed to be your acceptance of such change.

If any of these Terms and Conditions should be determined to be invalid, illegal or unenforceable for any reason by any court of competent jurisdiction then the applicable provision shall be severed and the remaining provisions of these Terms and Conditions shall survive and remain in full force and effect and continue to be binding and enforceable.

These Terms and Conditions shall: (i) be governed by and construed in accordance with the laws of the province of Alberta and you hereby submit to the exclusive jurisdiction of the Alberta courts, and (ii) ensure to the benefit of, and be binding upon, the Government of Alberta and your respective successors and assigns.



Heavy Oil

Controlled Document

Quest CCS Project

# Quest Power Efficiency and Parasitic Loss Summary

<b>Project</b>	Quest CCS Project
<b>Document Title</b>	Quest Power Efficiency and Parasitic Loss Summary
<b>Document Number</b>	
<b>Document Revision</b>	0
<b>Document Status</b>	Operate – First Issue
<b>Document Type</b>	
<b>Control ID</b>	New
<b>Owner / Authors</b>	Stephen Tessarolo
<b>Issue Date</b>	January 27, 2017
<b>Expiry Date</b>	None
<b>ECCN</b>	None
<b>Security Classification</b>	None
<b>Disclosure</b>	None

*Revision History shown on next page*

## Revision History

REVISION STATUS			APPROVAL		
Rev.	Date	Description	Originator	Reviewer	Approver
0	January 27, 2017	Issued for Knowledge Sharing Report	Stephen Tessarolo	Wilfried Maas	

## Signatures for this revision

Date	Role	Name	Signature or electronic reference (email)

## Summary

This document provides a high level overview of Quest compressor efficiency and a discussion around parasitic losses in Quest.

## Keywords

Quest, CCS, CO2, parasitic, power, compressor

## DCAF Authorities

Date	Role	Name	Signature or electronic reference (email)

Quest Power Efficiency and Parasitic Loss Summary		01
Heavy Oil		

**TABLE OF CONTENTS**

1. POWER EFFICIENCY AND PARASITIC LOSS SUMMARY .....4  
 1.1. Quest Power Consumption – Normal Operating .....4  
 1.2. Non-Compressor Driver Primary Loads vs Parasitic Loads .....5  
 1.3. CO<sub>2</sub> Compressor Efficiency Summary .....6

Quest Power Efficiency and Parasitic Loss Summary		01
Heavy Oil		

## 1. POWER EFFICIENCY AND PARASITIC LOSS SUMMARY

This report presents a summary of the parasitic power losses associated with electrically driven equipment in Quest, and presents an efficiency overview of the CO<sub>2</sub> compressor, C-24701 for the first 15 months of operation (August 2015 – November 2016).

### 1.1. Quest Power Consumption – Normal Operating

Power to the Quest unit is primarily provided via two sources – high voltage power to the CO<sub>2</sub> compressor, and a low voltage system to drive pumps, fans and auxiliary equipment on the Quest plot. Power to the Quest pipeline is provided by solar panels, and power to the wellsites is source from the local electrical grid, but is insignificant in terms of magnitude.

The primary power consumer in the Quest CCS process is the CO<sub>2</sub> compressor driver. The compressor is equipped with a 16.5 MW electric driver, with typical operation in the 12-15 MW range. The Quest plot itself, for other electrical loads such as pumps, fans, etc. consumes on the order of 4 MW at rated load. The following figure displays the power consumption of the Quest compressor and non-compressor electrical loads over time alongside CO<sub>2</sub> capture rates, in millions of tonnes/annum (Mt/a), over the first 15 months of operation.




Figure 1: Quest Power Consumption

Quest Power Efficiency and Parasitic Loss Summary		01
Heavy Oil		

The consumption rates are heavily dependent on throughput. For production rates greater than 1.05 Mt/a the compressor power consumption is proportional to throughput within the control range. Several of the non-compressor loads are also throughput dependent (pump/fan VFDs, etc.). For production rates less than 1.05 Mt/a the fixed speed compressor motor draws ~12 MW at turndown, and is equipped with inlet guide vanes to provide better efficiency when operating below full capacity on the machine. This base-load power consumption is a result of operating the compressor with the anti-surge (recycle) valve open to protect the machine from operating in a surge condition at low flow rates.

With the unit's design objective to run at higher capacities the lower efficiency on a per ton CO<sub>2</sub> basis at lower capacities is a result due to the nature of re-compressing gas that circulates through the machine to provide min flow/surge protection, but never enters the pipeline for transport to the injection wells for storage. Operation with the anti-surge valve open is an infrequent operating mode, and typically occurs only during low hydrogen demand periods at the Upgrader. Total electrical draw on the integrated Quest system has been as high as 19 MW during peak production periods, while turndown periods draw as little as 14 MW.

## 1.2. Non-Compressor Driver Primary Loads vs Parasitic Loads

As described in the previous section, non-CO<sub>2</sub> compressor electrical loads are a significant consumer of electricity in the Quest CCS unit, on the order of 4 MW at rated Quest capture unit capacity.

In the ADIP-x amine unit and TEG dehydration unit, electrical loads directly contributing to the capture/dehydration of CO<sub>2</sub> are loads such as those driving the amine circulation/charge pumps, water/condensate handling systems, chemical injection pumps, glycol circulation pumps, etc. These loads can be considered as primary electrical loads as their contribution directly results in the removal of CO<sub>2</sub> from the raw hydrogen streams in the HMUs, and dehydration of the CO<sub>2</sub> prior to transport to the wells. Table 1 provides a summarized breakdown of the electrical loads in the Quest capture unit.

Quest Power Efficiency and Parasitic Loss Summary		01
Heavy Oil		

Table 1: Non-Compressor Driver Electrical Load Summary

Electrical Load Type	MW
Amine/Glycol Circulation Pumps	2.3
Cooling Water Circulation Pumps	0.6
Condensate/Water Handling Pumps	0.1
Compressor Interstage Aerial Cooling, Lube oil heaters	0.2
Auxiliary Loads (EHT, HVAC, Lights, UPS/Instrumentation/Controls, transformer/MCC components)	0.8
Total Load @ Nameplate Capacity	~4.0

Chemical circulation (amine/glycol) is the largest normal power consumer around 2.3 MW, with power for the cooling water booster pumps in Quest as the next largest load around 0.6 MW. The lumped auxiliary loads at 0.8 MW above are effectively the parasitic loads in the context of the Quest capture unit. These are loads that continue to consume electricity when the amine unit/compression/dehydration units are not performing the task of capturing CO<sub>2</sub> with the purpose of transport for final storage. These loads vary seasonally, as EHT (electric heat tracing – primarily for freeze protection) will pull significantly more load in the winter and is typically offline in the warmer summer months. HVAC loads (heating ventilation and air conditioning) also vary seasonally given ambient conditions to maintain the capture unit buildings in the desired temperature range for safe/reliable operation.

### 1.3. CO<sub>2</sub> Compressor Efficiency Summary

The primary consumer of electricity in the Quest CCS process is the 8-stage integrally geared centrifugal compressor. The compressor contains interstage cooling and knockout for water removal up to and including the 6<sup>th</sup> stage prior to TEG dehydration. The compressor was designed with the ability to compress low pressure CO<sub>2</sub> from near atmospheric conditions leaving the capture unit to over 12 MPa at a rate exceeding 1.3 Mt/a to the pipeline. To accomplish this, the compressor was equipped with an electrically driven motor with a rated load of 16.5 MW.

A study was conducted for the purpose of this report to compare the expected power consumption with the operational consumption and thus assess the efficiency performance of the CO<sub>2</sub> compressor against design. Table 2 outlines expected performance of the Quest CO<sub>2</sub> compressor for the rated design case, and then compares this against averaged operating performance over a 5-week steady operating period (August 13, 2016 through September 17, 2016).

Quest Power Efficiency and Parasitic Loss Summary		01
Heavy Oil		



For the design case, the expected compressor driver power consumption to bring the CO<sub>2</sub> from 0.13 MPaa to 12.4 MPaa was roughly 15.1 MW. This considered losses within the driver itself (expected efficiency of 98.4%), losses within the compressor from mechanical means (assumed 95% efficiency), and the compression power requirement of roughly 14.1 MW at a polytropic efficiency of 84.9% from the design case.

The polytropic efficiency is utilized in this situation as the standard efficiency measurement for multi-stage centrifugal compression since the dynamic nature of centrifugal compression is best represented by a polytropic process vs an isentropic/adiabatic process.

The expected parasitic loads on the system in this case are the electrical power losses that are not directly associated with bringing the pressure of the CO<sub>2</sub> up to pipeline transmission pressure. The following is a qualitative summary of the electrical power losses.

Driver (motor):

- Mechanical friction losses, shaft driven lube oil pump, motor space heaters, etc.

Compressor Mechanical Losses:

- Frictional losses from bearings, seals, gears, etc.

Compression Process:

- Non-ideal nature of compression, deviation from fully reversible compression, temperature rise across each stage, interstage cooling influences, anti-surge flow (not relevant in this case, but certainly during turndown operation), etc.

Quest Power Efficiency and Parasitic Loss Summary		01
Heavy Oil		

Table 2: Compressor operating conditions and energy performance, rated vs operating

Compressor Process Conditions and Energy Performance	Rated Design Case	Aug - Sep 2016 5 Weeks of Steady Operation
Suction Pressure	0.13 MPa	0.13 MPa
Discharge Pressure	12.4 MPa	10.6 MPa
Suction Temperature	36°C	31°C
Discharge Temperature (estimated/actual)	135°C	131°C
Flow to pipeline	1.30 Mt/a	1.27 Mt/a
Polytropic Efficiency	84.9%	~81.1% <sup>i</sup>
Compression Power Requirement <sup>ii</sup>	~14.1 MW	~13.7 MW
Mechanical Efficiency	95.0%	~93% (combined) <sup>iii</sup>
Driver Efficiency	98.4%	
Overall Efficiency <sup>iv</sup>	79.4%	~75.3%
Driver Power Consumption	15.1 MW	14.8 MW

To compare expected performance with actual, a case study of operation over a 5-week period beginning August 13, 2016 through September 17, 2016 was compared against design performance conditions. Total throughput was similar to the rated case (1.27 vs 1.3 Mt/a), discharge pressure was lower (10.6 MPa vs 12.4 MPa), and composition and interstage cooling conditions were slightly different.

The power required for compression and overall efficiency of the machine/driver/process were marginally lower than the design rated case. The combined driver/mechanical efficiency for the operating case appears to be very close to that of the design case (both in the 93% range). The polytropic efficiency for the operating case (estimated) was 81.1% vs the design 84.9% value, and is the primary reduction in overall compressor efficiency. This was not unusual since the operating pressure in the August – September 2016 dataset was significantly lower than that of the design case, and throughput was slightly lower as well. Overall efficiency of the machine was well within acceptable tolerance (79.4% design vs 75.3% operational).

<sup>i</sup> Polytropic efficiency for the operating case was estimated based on actual operating conditions to match stage-compression temperature performance using a Unisim simulation model.

<sup>ii</sup> Compressor power requirement was derived using Unisim Design Process Simulation, specifying polytropic efficiency from design case.

<sup>iii</sup> For the actual operating case, driver efficiency and mechanical efficiency are lumped together as independent measurements are not readily available.

<sup>iv</sup> Overall efficiency in this assessment has been considered as the product of the polytropic efficiency, mechanical efficiency, and driver efficiency.

Quest Power Efficiency and Parasitic Loss Summary		01
Heavy Oil		