

# INDEX

## A

### ACCELERATION

- Data on acceleration from stop · D-29
- Effects of grade · D-35
- Intersections · D-97, D-99
- Lanes · D-97, F-5, F-7, F-15, F-21, F-23, F-35
- Performance curves for heavy trucks on grades · B-70–B-79
- Speed-distance relationship for heavy trucks on grade · D-31
- Speed-distance relationship for passenger vehicles · D-30
- Speed-time relationship for passenger vehicles · D-32

### ACCESS

- Design classifications · I-19
- Temporary means of · I-17
- Types · I-19
- Unauthorized means of · I-16

### ACCESS MANAGEMENT GUIDELINES · See Chapter I

- Access management by design classification · I-20
- Administration
  - municipal jurisdiction · I-16
  - provincial jurisdiction · I-16
  - temporary means of access · I-17
  - unauthorized means of access · I-16
- Design standards and guidelines for access treatment · I-33
- Land use management · I-15
- Roadway jurisdictions, design classifications and access types · I-18

### ACCIDENTS

- At intersection · D-7
- In roadside area · C-36
- On steep grades · B-60

### AESTHETICS · B-5

### ALIGNMENT

- General · B-5

### ALIGNMENT-HORIZONTAL · B-13

- Combination with vertical alignment · B-14, B-15
- Design speed · A-14
- Divided highways · A-14
- General controls · B-13
- Illustrations · B-15–B-26
- Intersections at grade · D-14
- Maximum superelevation · B-27
- Minimum radius · B-27
- Passing sight distance · B-8
- Rates of superelevation for design · B-28
- Sight distance · See SIGHT DISTANCE
- Spiral curves · B-39

### ALIGNMENT-VERTICAL

- Accidents · B-60
- Broken-back curves · B-45
- Combination with horizontal · B-45
- Critical lengths of grade · B-61
- Curbed roadways · B-47
- Curves · See CURVES-VERTICAL
- General controls for · B-45

- Intersections at grade · D-18
- Maximum gradient · B-46
- Minimum gradient · B-47
- Railway grade crossings · C-111
- Vertical curves · See CURVES-VERTICAL

### APPROACH

- Sideslopes · G-16–G-18
- Treatment of approaches on highways · G-16–G-18

### ARTERIALS

- Characteristics · A-5
- Definitions · A-5–A-9
- Desirable maximum gradients · A-21, B-46
- Lane width · A-21, C-9
- Level of Service · A-23
- Shoulders · A-21, C-10
- Speed · See DESIGN SPEED
- Two-lane to four-lane development · A-23, A-24

### AT-GRADE INTERSECTIONS, Chapter D

- Auxiliary lane
  - at divided highway intersections · D-172–D-193
  - at undivided highway intersections · D-89
  - climbing lanes · See CLIMBING LANES
  - length · D-89
  - passing · See PASSING LANES
  - warrant for channelization (undivided) · D-171, D-172
  - warrant for left turn (divided) · D-178
  - warrant for left turn (undivided) · D-139
  - warrant for right turn (divided) · D-179
  - warrant for right turn (undivided) · D-171, D-172
  - width · C-9

### AVERAGE ANNUAL DAILY TRAFFIC · A-16

## B

### BARRIERS · See TRAFFIC BARRIERS

### BRAKING

- Comfortable braking · D-89
- Distance (stopping sight distance) · B-7
- Effects of grades · D-91
- Perception-reaction time · B-6

### BRIDGE DETOURS · B-94

### BRIDGES

- Clearances · C-119–C-120

### BUS STOPS · C-74

- Rural · C-74
- Shelters · C-79

### BUS TRANSFER STATIONS · C-80

### BUSES

- Classification · D-38–D-40

**C**

## CAPACITY

- DHV · A-16
- General · A-23

## CHANNELIZATION

- At intersections · D-91
- Definition · D-91
- Design principles · D-91
- Islands · D-92
- Roadway width · D-96
- Warrants for · D-171, D-172

## CHANNELS

- Drainage · C-17

## CLASSIFICATION SYSTEM

- Service Classification System · A-5

## CLEAR ZONE · C-37

## CLEARANCES

- At structures · C-119–C-120
- On curve, for sight distance · B-42

## CLIMBING LANES

- Critical lengths of grade · B-61
- Cross slope · B-55
- Design example · B-63, B-68
- Ending of · B-55
- Four-lane highways warrant · B-68
- General · B-55
- Location of · B-68
- Marking · B-58
- Mass/power ratios · B-61
- Proximity to intersections · B-55
- Shoulders · B-55
- Sight distance · B-56
- Signing · B-58
- Start point · B-55
- Tapers · B-55
- Trucks · B-61
- Two-lane highways warrant · B-61
- Width · B-55

## CONSTRUCTION

- Transitions, two to four lane · B-84

## CROSS SLOPE

- Drainage · C-17
- Four-lane highways · C-7
- Gravel surface · C-7
- Maximum (superelevated) · B-27
- Minimum · C-7
- Normal · C-7
- Pavement · C-7
- Rollover, control for · D-105
- Six-lane highways · C-7
- Two-lane highways · C-7

## CROSSING SIGHT DISTANCE · D-27

- Acceleration curves · D-30–D-32
- Acceleration from stop · D-29
- Distance · D-27
- Minimum required · D-27
- Perception-reaction time · D-27

## CROSSOVER CROWN LINE · D-105

## CROSS-SECTION

- Cross-slope · *See* CROSS-SLOPE

Curb and Gutter · C-84

Divided highways

- rural · C-47
- semi-urban · C-47
- standard plans · C-93, C-95

Drainage · *See* DRAINAGE

Lane widths · C-9

Medians · C-47

Shoulders · C-10

Standard plans · C-88

Strategies to retain existing pavement widths · C-89, C-90

Two-lane rural cross-sections · C-86–C-110

## CROWN · C-7

Crossover crown line · D-105

## CULVERTS

Camber · C-29, C-31

Class of reinforced concrete pipes · C-21

Installation · C-23

Invert level · C-29

Riprap · C-33

Sloped end installations · C-25, C-26, C-27

Strength requirements · C-19

Type · C-19

## CURBS · C-84

Gutter · C-84, C-86

Mountable · C-84

Ramps · C-72

## CURVES-HORIZONTAL

Broken-back · B-14, B-15

Design speed · A-14

Friction factors · B-27

General controls · B-13

Intersection · D-13, D-14

Maximum curvature · B-27

Sight distance on · B-42

Spiral curves · B-39

Superelevation · *See* SUPERELEVATION

## CURVES-INTERSECTION

Choice of design vehicle · D-55

Edge of pavement design (three-centred curves) · D-58

Minimum designs for sharpest turn · D-56

Minimum radii (for design vehicles) · D-38, D-39

Turning templates · D-48–D-54

Two-centred curves · D-59

## CURVES-VERTICAL

Crest · B-48

- passing sight distance · B-51
- stopping sight distance · B-50

Drainage requirements on · B-47

General · B-48

General controls · B-45

K parameter · B-48

Maximum gradient · B-46

Minimum gradient · B-47

Sag · B-53

Sight distance on · B-48, B-49

---

**D**

**DECELERATION**

- At intersections · D-89
- Braking · D-89
- Effect of grade on length of deceleration lane · D-91
- Lanes · D-90
- Rates · D-90
- Treatment for · D-90
- Turning roadways · D-97

DEGREE OF CONGESTION · *See* Level of service

**DESIGN DESIGNATION** · A-10, A-11

- Criteria for selection · A-11

DESIGN ENVELOPE · *See* PEDESTRIAN ENVIRONMENTS

**DESIGN HOURLY VOLUME (DHV)** · A-16

**DESIGN LIFE** · A-16

**DESIGN SPEED**

- Definition · A-14
- Divided highways · A-14, A-15
- Expressway · A-14, A-15
- Freeways · A-14, A-15
- Local roads · A-15, H-6
- Selection · A-14
- Undivided highways · A-14, A-15

**DESIGN TRAFFIC VOLUME** · A-16

**DESIGN VEHICLES**

- Connections, A, B and C type · D-47
- Criteria for selection · D-55
- Definition · D-38
- Dimensions · D-40, D-41
- Height · D-41
- Log haul · D-62
- Long combination vehicle routes · D-43
- Median openings · D-175–D-177
- Minimum design for sharpest turn · D-56
- Minimum turning radii · D-38
- Three-centred curves · *See* THREE CENTRED CURVES
- Track width · D-48–D-54
- Truck combinations · D-45, D-50–D-53
- Turning templates · D-48–D-54
- Two-centred curves · D-59

**DETOURS**

- Bridge · B-94
- Design speed of · B-90
- Geometric parameters of · B-91
- Guidelines for surfacing of · B-89
- Horizontal alignment guidelines · B-90
- Superelevation for · B-92
- Temporary highway detours · B-89
- Typical cross-section for · B-93

**DIVIDED HIGHWAYS**

- Advantages · A-23
- Cross-sections · C-93, C-95
- Guidelines for twinning · A-23
- Median openings · D-175–D-177
- Medians · C-47
- Shoulders · C-10

**DRAINAGE**

- Channels · C-17
- Culverts · *See* CULVERTS
- Curb and gutter · C-84

- General · C-17
- Requirements · C-17
- Riprap · C-33

---

**E**

**ENVIRONMENTAL CONSIDERATIONS** · A-25

**EXPRESSWAY** · A-9

---

**F**

**FENCING** · C-122

- Construction · C-123
- Maintenance · C-123
- Requirement · C-122
- Type of · C-122

**FORMULAE**

- Spiral length · B-42

**FORMULAE**

- Braking distance · B-7
- Design hourly volume · A-16
- Effects of grade on acceleration · D-35
- Length of superelevation runoff · B-41
- Minimum radius · B-28
- Passing sight distance, elements of · B-9
- Sag vertical curves · B-54
- Sight distance
  - crest vertical curves · B-48
  - non-striping sight distance · B-52
  - passing sight distance · B-51
  - stopping sight distance · B-50
- Crest vertical curves
  - with intersections · D-37
- Sight triangle · D-25
- Spiral length · B-41
- Stop condition intersections
  - crossing · D-27
  - left turn · D-33

**FRICTION**

- Braking-stopping · B-7
- Side friction factors · B-27

**FRONTAGE ROADS**

- Example of typical intersection with four lane divided highway · D-193

---

**G**

**GRADE SEPARATION STRUCTURES**

- Clearances · C-119, C-120

**GRADES**

- Alignment coordination · B-45
- Arterials · A-21
- Climbing lanes · *See* CLIMBING LANES
- Critical lengths · B-61
- Effect on
  - acceleration · D-35
  - deceleration · D-91

sight distance, intersection · D-35  
 Intersections at grade · D-18  
 Local roads, maximum · H-8, H-13  
 Mass/power ratio · B-61  
 Maximum · B-46  
 Minimum · B-47  
 Vehicle operations on  
 passenger cars · D-18, D-30  
 trucks · B-60, D-31  
**GRADING**  
 Stage construction · C-109, C-110  
**GUARDRAIL**  
 Design of · C-45  
 Embankment warrant · C-42  
 Hazards to be mitigated · C-42  
 Installation on base course · C-45  
 Sideslope improvement to eliminate · C-44  
**GUTTER** · *See* CURBS

---

## H

**HEADLIGHT**  
 Height of · B-53  
**HEIGHT**  
 Eye · B-6  
 Headlight · B-53  
 Tail lights · B-6  
 Vehicles · B-6, D-40, D-41  
**HIGH LOAD CORRIDOR** · A-26  
 Map · A-29  
**HORIZONTAL ALIGNMENT** · *See* ALIGNMENT-  
 HORIZONTAL  
**HORIZONTAL CURVES** · *See* CURVES-HORIZONTAL

---

## I

**INFORMATION CENTERS** · F-14  
**INTERCHANGES** · E-3  
**INTERSECTION DESIGN ELEMENTS**  
 Alignment · D-13  
 Curves · D-13  
 Edge design · D-56  
 General · D-89, D-172  
 Human factors · D-9, D-27  
 Lighting · D-92, D-100  
 Median openings · D-175  
 Minimum designs for turns · D-56  
 Railway at-grade crossings · C-111  
 Sight distance · D-23  
 Turning roadways · D-96, D-100, D-105  
**INTERSECTIONS**  
 Acceleration · D-97  
 Accident experience · D-7  
 Angle · D-14  
 Approach treatment · D-18  
 Bulbing of service road · D-85  
 Bypass lanes · D-91  
 Comparison with interchanges · D-7

Conflicts · D-10  
 Cross slope · D-21  
 Deceleration · D-89  
 Definition · D-7  
 Design Principles · D-9  
 Flared · D-89  
 Geometric controls · D-13  
 Grades · D-18  
 Intersecting road · D-14, D-18  
 Main road · D-13, D-18  
 Median · C-47  
 Median openings · D-175  
 Minimum realignment criteria · D-14  
 Multi-lane highways · D-172  
 On curves · D-13  
 Provision for treatment · D-106, D-178, D-179  
 Reverse parabolic curb flares · D-174  
 Right/left hand forward · D-16  
 Shoulders · C-10  
 Sight distance · *See* SIGHT DISTANCE  
 Sight triangle · D-25  
 Signal control · D-35  
 Simple · D-89  
 Standard left-turn lanes · D-91  
 Storage length · D-141  
 Taper · D-89, D-172  
 Treatment type · D-111  
 Warrants  
 divided (left turn) · D-178  
 divided (right turn) · D-179  
 undivided (channelization) · D-171, D-172  
 undivided (general) · D-110  
 undivided (left turn) · D-139  
 undivided (right turn) · D-171, D-172  
 Width · D-27  
**ISLANDS**  
 Directional · D-92  
 Divisional · D-92  
 Refuge · D-93  
 Sight distance · D-91

---

## L

**LANES**  
 Left turning  
 description · D-91  
 warrant (divided) · D-178  
 warrant (undivided) · D-139  
 Right turning  
 description · D-90  
 warrant (divided) · D-179  
 warrant (undivided) · D-171, D-172  
 Widths · C-9  
**LENGTHS**  
 Auxiliary lanes at intersections  
 for acceleration at channelized intersections · D-97  
 for deceleration at channelized intersections · D-97  
 for deceleration at flared intersections · D-89  
 for storage at divided highway intersections · D-180  
 for storage at flared intersections · D-141

Curves  
vertical crest · B-48  
vertical sag · B-53  
Grades (performance charts) · B-70  
Minimum stopping sight distance · B-7  
Spirals · B-29  
Superelevation runoff · B-41  
Traveled by vehicle turning left to clear lane · D-33

LEVEL OF SERVICE  
Definitions · *See* Glossary

LOCAL ROADS  
Alignment · H-8  
Alignment control for · H-8  
Backslopes · H-23  
Cost effectiveness · H-5  
Design speed · H-6  
Ditches · H-23  
Drainage structures · H-23  
General · H-5  
Grades · H-13  
Maximum gradient · H-13  
Number of lanes · H-21, H-22  
Posted speed · H-7  
Sideslopes · H-22  
Sight distance · H-9  
Spiral curves · H-13  
Standard cross-section · H-17  
Superelevation · H-10  
Superelevation table · H-12  
Traffic volume ranges · H-5  
Vertical curves · H-13  
Widths · H-21

---

## M

MARKINGS  
Approach nose treatment (Gore) · E-5, E-7, E-9  
Climbing lanes · B-58  
Grooving · C-13  
No-passing · B-11  
Passing lanes · B-58  
Railway at-grade crossings · C-117  
Shoulders · C-13

MEDIAN  
Cross-section · C-47, C-93, C-95  
Depressed · C-47  
For ultimate development of highway · C-47  
General · C-47  
Left turns · D-178  
Raised · C-47  
Storage · D-180  
Taper · D-172  
Transitions for median widening · D-179  
Width at intersections · D-77

MEDIAN OPENINGS  
Above minimum design for direct left turns · D-175  
Bullet nose · D-175  
Control radii · D-175  
Design for cross traffic · D-77  
Design for left turns, minimum · D-175

Effect of skew on · D-178  
Flat nose · D-175, D-177  
General · D-175  
Semi-circular opening · D-175

MULTI-LANE HIGHWAYS · *See also* DIVIDED HIGHWAYS  
Climbing lanes · B-68  
Cross slope · C-7  
Intersections with · D-172  
Pavement width · A-21, C-9, C-10, C-95

---

## N

NON-STRIPING SIGHT DISTANCE · B-11

---

## O

OFF-ROADWAY ELEMENTS  
Roadside Facilities · Chapter F

OVERPASSES  
Overhead bridge · C-119

---

## P

PASSENGER CAR  
Acceleration · D-29, D-30, D-32  
Design vehicle · D-38  
Turning path · D-49

PASSING LANES  
Spacing of · B-83  
Warrant · B-80

PASSING SIGHT DISTANCE · B-8  
Design values · B-10  
General · B-8  
Measuring · B-10  
Model · B-8

PEAK-HOUR TRAFFIC · A-16

PEDESTRIAN ENVIRONMENTS · C-54  
Bus stops and bus transfer stations · C-68  
Design envelope · C-69  
Principles of effective orientation, wayfinding and warning · C-68  
Principles of mobility · C-68  
Streetscape · C-54  
Walkways · C-72

PERCEPTION REACTION TIME  
For intersection sight distance · D-33  
For stopping sight distance · B-6

PLANNING  
Future proposed freeways, expressways and interchanges · D-45  
Guidelines for Twinning · A-23

**R**

## RADII

- Intersection · D-13
- Minimum radius curves without superelevation · B-29, B-31
- Minimum turning · D-38
- Tables · B-29, B-31

## RAILWAY CROSSINGS

- Alignment and profile · C-111–C-113
- At-grade · C-111–C-117
- Drainage · C-121
- Grade separated · C-119
- Headslope toe · C-120
- Overpasses · C-119
  - clearance box · C-120
- Sight distance · C-114
- Underpasses · C-119
  - clearance box · C-120

## REST AREAS · F-13

- General · F-13
- Standard layouts · F-17, F-19, F-21, F-23, F-25, F-27, F-35

## RIGHT OF WAY

- Divided highways · C-48–C-53, C-93, C-95
- Fencing · C-122
- Provisions for ultimate conversion to four, six or eight lanes · C-48–C-53
- Width · A-21

## ROADSIDE

- Clear zone · C-37
- Forgiving roadside · C-36
- Hazards considered for mitigation · C-42
- Obstacles · C-43
- Permanent bodies of water · C-45
- Rounded ditch · C-40, C-41
- Sideslopes · C-44
- Traffic barriers · *See* TRAFFIC BARRIERS

## ROUNDING

- Ditches · C-40, C-41
- Shoulder · C-39

## RUMBLE STRIPS

- Grooved rumble strips on shoulders · C-11
- Milled rumble strips on shoulders · C-11

**S**

## SAFETY

- Effect of grades · B-60
- Intersections · D-7
- Recovery area · C-36
- Rest areas · F-13
- Shoulder grooving · C-11
- Warrants for sideslope improvement · C-44

## SERVICE CLASSIFICATION SYSTEM

- Descriptions/functions · A-5
- General · A-5

## SHOULDERS · C-10

- Adjacent to climbing lanes · C-10
- Cross slope, design values · C-7, C-8
- Divided highways · C-10

- Functions · C-10

## SIDE SLOPES

- Approaches on highways · G-16–G-18
- Channels, drainage · C-18
- Erosion prevention · C-17, C-33
- Safety · C-18

## SIGHT DISTANCE · B-5, B-6

- Criteria for measuring · B-6
- Crossing · *See* CROSSING SIGHT DISTANCE
- Decision · D-35
- Departures · D-27
- For left turn · D-34
- Formulae for determination · D-28
- General · B-5
- Intersections at grade · D-23
- Minimum for left turn · D-33
- Non-striping · *See* NON-STRIPING SIGHT DISTANCE
- Passing · *See* PASSING SIGHT DISTANCE
- Railway at-grade crossing · C-111–C-117
- Stopping · *See* STOPPING SIGHT DISTANCE

## SPEED · A-14

- Design · A-14
- Trucks on grades · B-70–B-79

## SPEED-CHANGE LANES

- Acceleration lanes · D-99
- Deceleration lanes · D-90, D-98
- Deceleration rates · D-89, E-5
- Deceleration requirements · D-89
- Length · D-90, D-98, D-99
- Ramps · E-5, E-7, E-9
- Warrants · D-139, D-171, D-172

## SPIRAL CURVES · B-39

- Aesthetics · B-42
- Basis of design · B-39
- Comfort · B-41
- Design values for spiral parameter · B-42
- Form and properties · B-39
- Superelevation runoff · B-41

## STOPPING SIGHT DISTANCE · B-6

- Crest · B-50
- General · B-6
- Measuring · B-6
- On vertical curves · B-50
- Perception-reaction time · B-6
- Sag · B-54
- Trucks · B-6
- Wet pavement · B-6

## SUPERELEVATION · B-28

- Crossover crown line · D-105
- Design rates · B-28
- Detours · B-92
- Development of · B-35
- Distribution of e and f · B-33
- Friction factor · B-27
- Maximum rate · B-27
- Maximum rates
  - on at-grade intersections · B-29, D-13
  - on climbing lanes · B-55
- Rates for design · B-28
- Runoff · B-41
- Tables · B-29, B-31

---

**T**

TANGENT RUNOUT · B-36, B-37

TAPER

- Bypass lanes · D-91
- Climbing and passing lanes · B-55
- Left turn (divided) · D-172
- Right turn (divided) · D-172
- Right turn (undivided) · D-90
- Turning roadway terminals · D-98, D-99

THREE CENTRED CURVES · D-60

- Asymmetric · D-60
- Data for · D-58
- Formulae · D-60
- Symmetric · D-60

TRAFFIC

- 30th highest hourly volume · A-16–A-17, A-19
- Design hourly volume (DHV) · A-16
- Design year · A-16
- Projection (growth) · A-11
- Speed · A-14

TRAFFIC BARRIERS

- Barrier warrants for fill slopes · C-44
- Definition · C-45
- Design guide · C-45

TRUCKS

- Acceleration · D-29
- Climbing lanes · B-55
- Deceleration on grades · B-61, B-70–B-79
- Height of eye · D-40
- Long combination routes · D-43
- Minimum designs for sharpest turn · D-56
- Off tracking · D-48–D-54
- Stopping sight distance · B-7

TURNING

- Indirect left turn for log haul · D-83
- Radius, minimum · D-38
- Speed · D-38

TURNING ROADWAYS

- Acceleration lanes · D-97
- Crossover crown line · D-105
- Curvature for · D-100
- Deceleration lanes · D-97
- Islands · D-92
- Superelevation at · D-105
- Width · D-96

TURNOUTS · F-13

TWINNING

- Guidelines · A-23

TWO CENTRED CURVES · D-61

- Data for · D-59
- Formula for · D-61

TWO-LANE HIGHWAYS

- Levels of service · A-23
- Passing lanes · B-80
- Passing sight distance · B-8

---

**U**

UNDERPASSES · C-119

---

**V**

VEHICLE INSPECTION STATIONS (VIS) · F-3

VEHICLES · *See* DESIGN VEHICLES, TRUCKS, TURNING

VERTICAL ALIGNMENT · *See* ALIGNMENT-VERTICAL

VERTICAL CURVES · *See* CURVES-VERTICAL

---

**W**

WALKWAYS · C-72

WARRANTS

- Climbing lanes · B-59
  - for four lane divided · B-68
  - for two lane undivided · B-61
- For twinning on two lane roads · A-23
- Improvements for existing paved roads
  - grade widening · G-8
  - horizontal curvature · G-10
  - intersections · G-14
  - sideslopes · G-16, G-17
  - slopes on high embankments · C-44
  - superelevation · G-19
  - vertical alignment (crests) · G-11
  - vertical alignment (sags) · G-12, G-13

Intersection treatment

- Left turn lane (divided) · D-178
- left turn lane (undivided) · D-139
- Right turn lane (divided) · D-179
- right turn lane (undivided) · D-171, D-172

Passing lanes · B-80

Roadway width

- existing paved roads (suggested minimum) · G-9
- new construction (desirable) · A-12

WEAVING

- Length · E-5

WIDENING

- Warrants for paved roads · G-8

WIDTH

- Arterials · A-12
- Clear zone · C-37
- Climbing lanes · B-55
- Gutter · C-84
- Lanes · A-21, C-9
- Passing lanes · B-55
- Right of way · A-21
- Shoulders · A-21, C-10
- Strategies to retain existing pavement widths · C-87
- Track · D-48–D-54
- Turning roadways · D-96

*This page left blank intentionally.*